

A/C SERVICE STATION

冷媒回收加注机

A/C RECOVERY & RECHARGE

冷媒回收加注机

EXPLORER SERIES

勇士系列



AC616



AC626



AC636



AC636YF



AC616H



AC636H

Product Code Definition

型号命名规范

AC6_6_

None - Fuel vehicle of refrigerant R134a

无字母时表示适用燃油车型空调，R134a冷媒

H - Hybrid vehicle

H表示适用于混合动力车型空

YF - Vehicle of new refrigerant R1234yf

YF表示适用于R1234yf新冷媒车型空调

1 - Automatic 自动

2 - Full automatic 全自动

3 - Full automatic+ Vehicle data base+Printer

全自动，带车型数据库，带打印机

A/C RECOVERY & RECHARGE

冷媒回收加注机

EXPLORER SERIES
勇士系列



Refrigerant
Recovery
冷媒回收

Vacuum
空调抽真空

Refrigerant
Recharge
冷媒加注



AC616H



AC636H

PARAMETERS 参数

Model 型号	AC616H	AC636H
Suit for 适用车型	Hybrid vehicles	Hybrid vehicles
Refrigerant 适用雪种	R134a	R134a
Mode 模式	Automatic	Fully-automatic
Voltage 电源	AC220v/50hz/1ph	AC220v/50hz/1ph
Screen 屏幕	3.2" LCD	3.9" LCD
Recovery speed 回收速度	180~350G/min	180~350G/min
Recharge speed 加注速度	800~1500G/min	800~1500G/min
Vacuum speed 抽真空速度	60L/min	60L/min
Refrigerant tank available capacity 冷媒罐容积	14 L	14 L
Electronic scale range 冷媒电子称量程	40KG	40KG
Oil bottle capacity 冷冻油油瓶容积	300ML	300ML
Operating temperature 工作温度	5~50℃	5~50℃
Max. working pressure 最大工作压力	17.5bar	17.5bar
Electronic scale precision 冷媒加注精度	± 10g	± 10g
Compressor 压缩机	275w	275w

A/C RECOVERY & RECHARGE

冷媒回收加注机

EXPLORER SERIES
勇士系列

Refrigerant
Recovery
冷媒回收

Vacuum
空调抽真空

Refrigerant
Recharge
冷媒加注



AC616



AC626



AC636



AC636YF

PARAMETERS 参数

Model 型号	AC616	AC626	AC636	AC636YF
Suit for 适用车型				
Refrigerant 适用雪种	R134a	R134a	R134a	R1234YF
Mode 模式	Automatic	Fully-automatic	Fully-automatic	Fully-automatic
Voltage 电源	AC220v/50hz/1ph	AC220v/50hz/1ph	AC220v/50hz/1ph	AC220v/50hz/1ph
Screen 屏幕	3.2" LCD	3.9" LCD	3.9" LCD	3.9" LCD
Recovery speed 回收速度	180~350G/min	180~350G/min	180~350G/min	180~350G/min
Recharge speed 加注速度	800~1500G/min	800~1500G/min	800~1500G/min	800~1500G/min
Vacuum speed 抽真空速度	60L/min	60L/min	60L/min	90L/min
Refrigerant tank available capacity 冷媒罐容积	14 L	14 L	14 L	14 L
Electronic scale range 冷媒电子称量程	40KG	40KG	40KG	40KG
Oil bottle capacity 冷冻油油瓶容积	300ML	300ML	300ML	300ML
Operating temperature 工作温度	5~50℃	5~50℃	5~50℃	5~50℃
Max. working pressure 最大工作压力	17.5bar	17.5bar	17.5bar	17.5bar
Electronic scale precision 冷媒加注精度	± 10g	± 10g	± 10g	± 10g
Compressor 压缩机	275w	275w	275w	3/8HP