

DIGITAL METER OIL CONTROL VALVE

电子流量加注枪

Oil Control Valve

无显示机油加注枪



80970011



80970025

Anti-drip nozzle
防滴漏油嘴



80970035

Updated universal design
with anti-drip nozzle
全新万向转动设计
防滴漏油嘴

Digital Meter

Oil Control Valve

数显式机油加注枪

- Battery indicator
显示电池容量



80981011



80981025

Anti-drip nozzle
防滴漏油嘴



80981035

Updated universal design
with anti-drip nozzle
全新万向转动设计
防滴漏油嘴

Pre-Digital Meter

Oil Control Valve

预设式机油加注枪

- Electronic card with LCD housed in cover
液晶显示集成电脑板
- 5-digit liquid crystal display
5位数字显示
- 4 units of measurement: L/ GAL/ PT/ QT
4种计量单位: L/ GAL/ PT/ QT



80999011



80999025

Anti-drip nozzle
防滴漏油嘴



80999035

Updated universal design
with anti-drip nozzle
全新万向转动设计
防滴漏油嘴

DIGITAL METER OIL CONTROL VALVE

电子流量加注枪

Aluminum nozzle made by special
process, light and strong.
铝制油嘴，经过特殊工艺，
表面处理，轻捷、坚固。

The nozzle equipped non-drip
device to fix the oil leakage
problem perfectly.
枪嘴配置防滴漏泄压装置，解决
枪嘴渗油问题

The nozzle automatically closed
the valve by stepping motor
control, high sensitivity with long
service life. Power save 30%
compares with those by
electromagnetic lock.
采用步进电机控制，反应更敏捷，
计量更精确，使用寿命长。

The item is an integral forming
design, reduce oil leak risk.
枪体一体成型，减少接头连接，
降低漏油风险；

Rotating join
油管旋转接头

Anti-leaking decompression
button
防滴漏泄压按钮

Metal tube
金属管

Adopt omni-directional pole design,
suits for various workplace.
采用万向转动枪杆机构，产品适用于更
多工作场所；

Automatic shut down protection
is provided if the item is idle for
1 minute, in order to save power.
连续1分钟无操作，机器自动断电屏保，
避免电池电量损耗；

Pre-selected function for accurate
dispensing.
全新设计定量驱动模式

Anti-slip handle
防滑手柄

80999035

PARAMETERS 参数

Model 型号	80970025	80970035	80981025	80981035	80999025	80999035
Pre-selectable quantity 预设范围	/		/		0.1L min, 99.9L max	
Flow rate 流量范围	1 to 25L/min		1 to 25L/min		1 to 30L/min	
Precision 加注精度范围	/		± 0.3%		± 0.3%	
Max working pressure 最高工作压力	70 bar		70 bar		70 bar	
Min working pressure 最低工作压力	3 bar		3 bar		3 bar	
Input with rotating 进油口旋转接头	1/2" BSP/NPT		1/2" BSP/NPT		1/2" BSP/NPT	
Meter body input/output 流量表进出口接头	1/2" BSP/NPT		1/2" BSP/NPT		1/2" BSP/NPT	
Inner diameter 内径	φ10		φ10		φ10	
Power supply 电压	/		DC 3V		DC 6V	
Outlet tube type 出油管	flexible hose 软管	Rigid tube 金属管	flexible hose 软管	Rigid tube 金属管	flexible hose 软管	Rigid tube 金属管
Spout 枪嘴	Automatic 自动（防滴漏）		Automatic 自动（防滴漏）		Automatic 自动（防滴漏）	